

2i-M OFFICE WATER FILL STATION



STATE-OF-THE-ART PURIFICATION TECHNOLOGY

On-board, multi-stage, reverse osmosis purification.



OPTIMAL DISPENSE HEIGHT & AREA

Ergonomic design for “no-bend” dispensing.
Spacious dispense area for larger refillable bottles.



CLEANCONTACT™ ANTI-MICROBIAL TOUCHPAD

Organic anti-microbial coating helps maintain the cleanliness of touch-pad.



24/7 SYSTEM MONITORING

Diagnostic center ensures system performance and water quality.



DISPENSE AREA LIGHT

Enables precise dispensing and reduced likelihood of spillage.



DENT-RESISTANT

Strong metal frame resists dents and damage.



INDUSTRY-LEADING CERTIFICATIONS

The 2i Water Fill Station is manufactured in an ISO 9001/14001 facility and certified to meet UL standards.



Now available with
touchless-dispense
options!

2i OFFICE WATER FILL STATION

Our Traditional Product Series

2i Specifications



Description	Specification
Weight	62 lbs (28 kgs)
Dimensions	13" W x 18.2" D x 49.7" H (330.2mm W x 462.3mm D x 1262mm H)
Cold Tank Capacity	2.0 gallons (7.5 Liters)
Hot Tank Capacity	0.5 gallons (1.8 Liters)
Dispense Area	9" H (229mm H)
Reverse Osmosis Membrane Capacity	80 gallons per day
Reccomended Water Pressure	Do not exceed 60 psi
Rated Voltage/ Frequency	120v/60hz 220v/50hz
Power Consumption	Hot: 300W Cold: 100W

The Pure Water Technology Filtration Process

