

Ultrafiltration System | UFL



Improve the quality of drinking water throughout the home and decrease the number of maintenance issues that are caused by poor water quality with the UFL ultrafiltration system.

The UFL systems feature an ultrafiltration cartridge that substantially reduces particles from the water. The system is self-cleaning, which extends the life of the ultrafilter and allows it to operate with little user intervention.

NOTE: The Flush Tank Kit (P/N 7000472) is highly recommended to improve the flushing function and extend the life of the ultrafilter.

NOTE: Additional taste and odor and scale reduction systems are also available.

FEATURES

- .015 micron ultrafiltration significantly reduces particles, assuring consistent, high-quality water.
- Self-cleaning capabilities extend the life of the ultrafilter.
- Operation simplicity.
- Several sizes available to meet various flow rates.



UFL-420, UFL-440 tested and certified by NSF International against NSF/ANSI:
Standard No. 42: Aesthetic Effects
Nominal Particulate Reduction
Class 1.
Standard No. 53: Health Effects
Cyst Reduction Turbidity Reduction
as verified and substantiated by
test data.



Ultrafiltration System | UFL

UFL systems significantly reduce particles from water, yielding filtered water and fewer maintenance issues related to poor water quality. With a small footprint, these systems have added flexibility for easy installation.

- Maximum Operating Pressure: 100 psig (690 kPa)
- Maximum Operating Temperature: 104°F (40°C)
- Nominal Pore Size: .015 microns
- pH Range: 3 to 10
- MWCO: 100 kD
- Volts: 100 to 240
- Watts: 10
- Amps: 0.4
- Includes plug adaptors for US, Europe, Australia, and UK

Specifications

Model & Mfg. No.	Max. Flow Rate	UF Length	Inlet	Outlet	Drain	Width	Depth	Height	Operating Weight	Shipping Weight
PLX-510 9710125	5.2 gpm* (19 lpm)	10" (25 cm)	3/4" MNPT	3/4" MNPT	3/4" FNPT	12" (30.5 cm)	6 1/4" (19 cm)	23" (58 cm)	17 lbs. (7.7 kg)	19 lbs. (8.6 kg)
PLX-520 9710126	7.9 gpm** (29.1 lpm)	20" (51 cm)	3/4" MNPT	3/4" MNPT	3/4" FNPT	12" (30.5 cm)	6" (15 cm)	30" (76 cm)	23 lbs. (10.4 kg)	23 lbs. (10.4 kg)
PLX-540 9710124	15 gpm*** (57 lpm)	40" (102 cm)	3/4" MNPT	3/4" MNPT	3/4" FNPT	12" (30.5 cm)	6" (15 cm)	49" (124 cm)	42 lbs. (19.1 kg)	33 lbs. (15 kg)

*NSF certified at 5.2 gpm (19 lpm). **NSF certified at 7.9 gpm (29.1 lpm). ***NSF certified at 13 gpm (49.2 lpm).

Replacement Cartridges

Name	Description	Mfg. No.
L-510 Replacement Ultrafilter		7001915
L-520 Replacement Ultrafilter		7001917
L-540 Replacement Ultrafilter		7001916

Specifications

- /// Maximum Operating Pressure: 100 psig (690 kPa)
- /// Maximum Operating Temperature: 104°F (40°C)
- /// Nominal Pore Size: .015 microns
- /// pH Range: 3 to 10
- /// MWCO: 100 kD
- /// Volts: 100 to 240
- /// Watts: 10
- /// Amps: .4
- /// Includes plug adaptors for US, Europe, Australia & UK

P/N 1020250 07/17